

Combination Densitometers and Sensitometers



Model 6613 – Densonorm 21e

Sensitometer

- ▶ 21 density strip, D 0.15 per step
- ▶ Green 510 nm, blue 460 nm, switchable
- ▶ Regulated light source
- ▶ Repeatability better than 0.02 D

Densitometer

- ▶ Single point capability
- ▶ 20 cm (8 in) throat
- ▶ 3 mm aperture diameter
- ▶ 0.00 to 4.50 D range
- ▶ Accuracy is ± 0.01 D

General

- ▶ 9 V alkaline battery or AC adaptor
- ▶ Multi-language display (English, French, German)



Model 6626 – Densonorm 21i

Sensitometer

- ▶ 21 density strip, D 0.15 per step
- ▶ Green 510 nm, blue 460 nm, switchable
- ▶ Regulated light source
- ▶ Repeatability better than 0.02 D

Densitometer

- ▶ Single point with 20 cm (8 in) throat
- ▶ 3 mm aperture diameter
- ▶ 0.00 to 4.50 D
- ▶ Accuracy is ± 0.01 D

Scanning Densitometer

- ▶ Automatically scans 21 step film strip in less than 5s
- ▶ Immediately evaluates and displays: Speed index, Contrast index, Base fog, Maximum D, Relative speed, Average gradient, Light speed, Light contrast

General

- ▶ 9 V alkaline battery or AC adaptor
- ▶ Multi-language display (English, French, German)
- ▶ RS-232 port